DRAFT FOR CONSULTATION

Telecommunications (Regulated Fibre Services) Regulations 2021

Governor-General

Order in Council

At Wellington this

day of

2021

Present:

in Council

These regulations are made under sections 226, 227, and 228 of the Telecommunications Act 2001—

- (a) on the advice and with the consent of the Executive Council; and
- (b) on the recommendation of the Minister for the Digital Economy and Communications given in accordance with sections 226, 227, and 228 and clauses 13 to 15 of Schedule 1AA of that Act.

Contents

| | | U |
|----|---|---|
| 1 | Title | 2 |
| 2 | Commencement | 2 |
| 3 | Interpretation | 2 |
| 4 | Transitional, savings, and related provisions | 3 |
| 5 | Overview | 3 |
| | Anchor services | |
| 6 | Anchor services | 3 |
| 7 | Broadband anchor service—description of service | 3 |
| 8 | Broadband anchor service—maximum price | 4 |
| 9 | Additional document references for broadband anchor service | 4 |
| 10 | Voice anchor service—description of service | 5 |
| | | |

Page

| r 1 | Telecommunications (Regulated Fibre Services) Regulations 2021 | |
|-----|--|----|
| 11 | Voice anchor service—maximum price | 5 |
| 12 | Additional document references for voice anchor service | 5 |
| | Direct fibre access services | |
| 13 | Direct fibre access services | 6 |
| 14 | Large-user direct fibre access service—description of service | 6 |
| 15 | Large-user direct fibre access service—maximum price | 7 |
| 16 | Additional document references for large-user direct fibre access service | 7 |
| | Amendments to Telecommunications (Regulated Fibre Service Providers) Regulations 2019 | |
| 17 | Principal regulations | 7 |
| 18 | New regulation 4A inserted (Overview) | 7 |
| | 4A Overview | 7 |
| | Schedule 1 Transitional, savings, and related provisions | 8 |
| | Schedule 2 Modifications to documents incorporated by reference | 9 |
| | Schedule 3 Technical standards cited in service descriptions | 19 |
| | | |

Regulations

1 Title

These regulations are the Telecommunications (Regulated Fibre Services) Regulations 2021.

2 Commencement

These regulations come into force on 31 December 2021.

3 Interpretation

In these regulations, unless the context otherwise requires,-

Act means the Telecommunications Act 2001

broadband anchor service has the meaning set out in regulation 6(a)

Broadband Anchor Service Description means the Chorus UFB Services Agreement (Service Description for Bitstream 2 Accelerate) Reference Offer dated June 2017, including the modifications set out in Schedule 2

Large-User DFAS Service Description means the Chorus UFB Services Agreement Direct Fibre Access Services (Service Description for Direct Fibre Access Service) Reference Offer dated April 2021, including the modifications set out in Schedule 2 large-user direct fibre access service has the meaning set out in regulation 13(1)

voice anchor service has the meaning set out in regulation 6(b)

Voice Anchor Service Description means the Chorus UFB Services Agreement (Service Description for Baseband) Reference Offer dated June 2017, including the modifications set out in Schedule 2.

4 Transitional, savings, and related provisions

The transitional, savings, and related provisions (if any) set out in Schedule 1 have effect according to their terms.

5 Overview

- (1) These regulations declare certain fibre fixed line access services to be anchor services or direct fibre access services, with the result that a person who is subject to price-quality regulation must provide those services under the Act (*see* sections 198 and 199).
- (2) See also the Telecommunications (Regulated Fibre Service Providers) Regulations 2019, which prescribe the persons who are subject to price-quality regulation under the Act.
- (3) This regulation is only a guide to the general scheme and effect of these regulations.

Anchor services

6 Anchor services

For the purposes of section 227(1) of the Act, the following services are declared to be anchor services:

- (a) a broadband internet access service with a minimum download speed of 100 megabits per second and a minimum upload speed of 20 megabits per second, provided in accordance with regulations 7 and 8 (the broadband anchor service):
- (b) a voice-only communication service provided using an ultra-fast broadband internet connection, provided in accordance with regulations 10 and 11 (the **voice anchor service**).

7 Broadband anchor service—description of service

- (1) This regulation applies for the purposes of section 227(2)(a) of the Act.
- (2) In relation to the broadband anchor service, the description of the service—
 - (a) is set out in the provisions of the Broadband Anchor Service Description identified in column 2 of item 1 of the following table, subject to the modifications set out in Schedule 2; and

(b) includes the technical specifications set out in the provisions of the Broadband Anchor Service Description identified in column 2 of item 2 of the following table, subject to the modifications set out in Schedule 2.

Table 1: service features for broadband anchor service

| | Column 1 | Column 2 |
|------|-------------------------|--|
| Item | Service feature | Provisions that service must comply with |
| 1 | Service description | Clauses 1 to 8 and Appendix A of the Broadband Anchor Service Description (subject to the modifications set out in Schedule 2) |
| 2 | Technical specification | Appendix B of the Broadband Anchor Service Description (subject to the modifications set out in Schedule 2) |

8 Broadband anchor service—maximum price

- (1) This regulation applies for the purposes of section 227(2)(d) of the Act.
- (2) The maximum price that a regulated fibre service provider who is subject to price-quality regulation may charge for the broadband anchor service, where the service is provided in respect of premises that are residential premises, is \$47.15 per month (subject to subclause (4)).
- (3) The maximum price applies in respect of each connection provided.
- (4) The maximum price increases or decreases (as appropriate) by an annual CPI adjustment on 1 January in each year (starting on 1 January 2023).
- (5) In this regulation,—

premises has the meaning given in section 2 of the Residential Tenancies Act 1986

residential premises means-

- (a) premises that are used or intended for occupation by a person principally as a place of residence; but
- (b) does not include premises that constitute any part of premises described in section 5(1)(c) to (k) of the Residential Tenancies Act 1986 (which refers to places such as jails, hospitals, hostels, hotels, and other places providing temporary accommodation).

9 Additional document references for broadband anchor service

- (1) For the purposes of regulation 7(2)(a) and (b), the following documents apply to the extent that they are relevant to the Broadband Anchor Service Description:
 - (a) the Chorus UFB Services Agreement (General Terms) dated December 2012:
 - (b) the Chorus UFB Services Agreement (Operations Manual for Bitstream Services) Reference Offer dated October 2020:

r 8

- (c) the Chorus UFB Services Agreement (Service Level Terms for Bitstream Services) Reference Offer dated October 2020:
- (d) the notice of points of interconnection, published by the Commerce Commission under section 231 of the Act and dated 19 December 2019:
- the TCF UFB Ethernet Access Service Description, version 33, dated 11 May 2017:
- (f) the technical standards listed in Part 1 of Schedule 3.
- (2) A document that is referred to in the Broadband Anchor Service Description or any of the documents in subclause (1), but that is not listed in subclause (1), has no legal effect for the purposes of regulation 7(2)(a) or (b).

10 Voice anchor service—description of service

- (1) This regulation applies for the purposes of section 227(2)(a) of the Act.
- (2) In relation to the voice anchor service, the description of the service—
 - (a) is set out in the provisions of the Voice Anchor Service Description identified in column 2 of item 1 of the following table, subject to the modifications set out in Schedule 2; and
 - (b) includes the technical specifications set out in the provisions of the Voice Anchor Service Description identified in column 2 of item 2 of the following table, subject to the modifications set out in Schedule 2.

Table 2: service features for voice anchor service

| | Column 1 | Column 2 |
|------|-------------------------|--|
| Item | Service feature | Provisions that service must comply with |
| 1 | Service description | Clauses 1 to 7 and Appendix A of the Voice Anchor Service Description (subject to the modifications set out in Schedule 2) |
| 2 | Technical specification | Appendix B of the Voice Anchor Service Description (subject to the modifications set out in Schedule 2) |

11 Voice anchor service—maximum price

- (1) This regulation applies for the purposes of section 227(2)(d) of the Act.
- (2) The maximum price that a regulated fibre service provider who is subject to price-quality regulation may charge for the voice anchor service is \$25.63 per month (subject to subclause (4)).
- (3) The maximum price applies in respect of each connection provided.
- (4) The maximum price increases or decreases (as appropriate) by an annual CPI adjustment on 1 January in each year (starting on 1 January 2023).

12 Additional document references for voice anchor service

(1) For the purposes of regulation 10(2)(a) and (b), the following documents apply to the extent that they are relevant to the Voice Anchor Service Description:

- (a) the Chorus UFB Services Agreement (General Terms) dated December 2012:
- (b) the Chorus UFB Services Agreement (Operations Manual for Bitstream Services) Reference Offer dated October 2020:
- (c) the Chorus UFB Services Agreement (Service Level Terms for Bitstream Services) Reference Offer dated October 2020:
- (d) the notice of points of interconnection, published by the Commerce Commission under section 231 of the Act and dated 19 December 2019:
- (e) the technical standards listed in Part 2 of Schedule 3.
- (2) A document that is referred to in the Voice Anchor Service Description or any of the documents in subclause (1), but that is not listed in subclause (1), has no legal effect for the purposes of regulation 10(2)(a) or (b).

Direct fibre access services

13 Direct fibre access services

- (1) For the purposes of section 228(1) of the Act, a dark fibre service that enables access to, and interconnection with, the LFC fibre network, and provided in accordance with regulations 14 and 15 (the large-user direct fibre access service), is declared to be a direct fibre access service.
- (2) In this regulation, LFC fibre network has the same meaning as in section 156AB of the Act.

14 Large-user direct fibre access service—description of service

- (1) This regulation applies for the purposes of section 228(2)(a) of the Act.
- (2) In relation to the large-user direct fibre access service, the description of the service—
 - (a) is set out in the provisions of the Large-User DFAS Service Description identified in column 2 of item 1 of the following table, subject to the modifications set out in Schedule 2; and
 - (b) includes the technical specifications set out in the provisions of the Large-User DFAS Service Description identified in column 2 of item 2 of the following table, subject to the modifications set out in Schedule 2.

Table 5: service features for large-user direct fibre access service

| | Column 1 | Column 2 |
|------|-------------------------|---|
| Item | Service feature | Provisions that service must comply with |
| 1 | Service description | Clauses 1 to 9 and Appendix A of the Large-User DFAS Service Description (subject to the modifications set out in Schedule 2) |
| 2 | Technical specification | Appendix B of the Large-User DFAS Service Description (subject to the modifications set out in Schedule 2) |

15 Large-user direct fibre access service—maximum price

- (1) This regulation applies for the purposes of section 228(2)(d) of the Act.
- (2) The maximum price that a regulated fibre service provider who is subject to price-quality regulation may charge for the large-user direct fibre access service is \$363.88 per month (subject to subclause (4)).
- (3) The maximum price applies in respect of each connection provided.
- (4) The maximum price increases or decreases (as appropriate) by an annual CPI adjustment on 1 January in each year (starting on 1 January 2023).

16 Additional document references for large-user direct fibre access service

- (1) For the purposes of regulation 14(2)(a) and (b), the following documents apply to the extent that they are relevant to the Large-User DFAS Service Description:
 - (a) the Chorus UFB Services Agreement (General Terms) dated December 2012:
 - (b) the Chorus UFB Services Agreement Direct Fibre Access Services (layer 1) (Operations Manual for Direct Fibre Access Services (layer 1)) Reference Offer dated October 2020:
 - (c) the Chorus UFB Services Agreement Fibre Access Services (layer 1) (Service Level Terms for Fibre Access Services (layer 1)) Reference Offer dated October 2020:
 - (d) the technical standards listed in Part 3 of Schedule 3.
- (2) A document that is referred to in the Large-User DFAS Service Description or any of the documents in subclause (1), but that is not listed in subclause (1), has no legal effect for the purposes of regulation 14(2)(a) or (b).

Amendments to Telecommunications (Regulated Fibre Service Providers) Regulations 2019

17 Principal regulations

Regulation 18 amends the Telecommunications (Regulated Fibre Service Providers) Regulations 2019.

18 New regulation 4A inserted (Overview)

After regulation 4, insert:

4A Overview

- These regulations prescribe persons who provide fibre fixed line access services as being subject to information disclosure regulation and price-quality regulation under the Act.
- (2) See also the Telecommunications (Regulated Fibre Services) Regulations 2021, which declare certain fibre fixed line access services to be anchor services or

direct fibre access services, with the result that a person who is subject to pricequality regulation must provide those services under the Act (*see* sections 198 and 199).

(3) This regulation is only a guide to the general scheme and effect of these regulations.

Schedule 1 Transitional, savings, and related provisions

r 4

There are no transitional, savings, or related provisions relating to these regulations as made.

Modifications to documents incorporated by reference

rr 7, 10, 14

Schedule 2

Broadband Anchor Service Description

Replace clauses 2.1 and 2.2 with:

- 2.1 The Bitstream 2 Accelerate Service is a bitstream service suitable for accessing a wide range of internet and bespoke applications and content delivered over a point to multipoint fibre access.
- 2.2 A diagram of the configuration for the Bitstream 2 Accelerate Service is set out in Appendix A. The Bitstream 2 Accelerate Service provides one Access-Ethernet Virtual Private Line (Access-EVPL) Operator Virtual Circuit (OVC) from the UNI on the ONT located at the End User Premises to the UFB Handover Connection Service located at the POI that enables a Service Provider to access and interconnect with the LFC network.

Replace clause 2.4 with:

- 2.4 The Bitstream 2 Accelerate Service has the following key characteristics:
 - 2.4.1 The Bitstream 2 Accelerate Service includes one Ethernet Access-EVPL bitstream service delivered in conjunction with Baseband over GPON. In particular:
 - (a) the Ethernet Access-EVPL bitstream service provides a single VLAN between the UNI and the E-NNI; and
 - (b) the Baseband service supports a single instance of the ATA Voice Service.
 - 2.4.2 Support for two classes of traffic, High Traffic Class and Low Traffic Class:

| Traffic Class | CIR | EIR |
|---------------|----------|----------|
| Low | ≥ 0 | ≥ 0 |
| High | ≥ 0 | = 0 |

- 2.4.3 Supports tagged or untagged frames at the UNI.
- 2.4.4 Optionally inserts Circuit ID information in DHCP (Version 4) and PPPoE traffic.
- 2.4.5 Complies with the Mass Market service specified in the TCF UFB Ethernet Access Service Description.

Replace clauses 3.5 to 3.7 (including the cross-heading above clause 3.5) with:

Additional Services

- 3.5 If the Service Provider requires additional services such as:
 - (a) any Premises wiring services; or
 - (b) installation and testing of Service Provider equipment and services,

Broadband Anchor Service Description—continued

then the LFC may be able to provide those items on request subject to terms to be agreed between the LFC and the Service Provider.

Core Bitstream 2 Accelerate Service

3.6 The core bitstream services provided as part of the Bitstream 2 Accelerate Service are as follows:

3.6.1 One Access-EVPL consisting of:

- (a) A single 802.1q VLAN on a designated UNI on the ONT at the End User Premises.
- (b) A single 802.1ad VLAN (Service VLAN ID/ Customer VLAN ID) on the E-NNI at the POI.
- (c) A QOS bandwidth profile that describes how traffic is carried between these points.
- 3.6.2 Bandwidth overhead for Low Traffic Class to compensate for higher protocol encapsulation overheads. The size of the overhead is calculated as follows:
 - (a) 10% overhead in Low Traffic Class bandwidth downstream; and
 - (b) 10% overhead in Low Traffic Class bandwidth upstream.

This maximum bandwidth (including overhead) does not guarantee End Users will experience the headline speed as their experience is dependent on a number of external factors including, but not limited to, End User applications and local network, the Service Provider network and location of the content they are accessing.

- 3.7 The Bitstream 2 Accelerate Service includes the options, exercised by Service Request, to:
 - 3.7.1 Set the UNI as a tagged or untagged interface.
 - 3.7.2 Enable Circuit ID, as specified in Broadband Forum TR-101/TR-156, per service instance. If this feature is requested, then Product Instance and TR-101 information will be embedded in DHCP or PPPoE traffic.
 - 3.7.3 If the UNI is set to untagged:
 - (a) Untagged frames sent from the End User are 802.1q tagged and marked as Low Traffic Class;
 - (b) Tagged frames sent from the End User are discarded; and
 - (c) 802.1q tags will be removed from downstream frames and presented as 802.3 Ethernet frames at the UNI.
 - 3.7.4 If the UNI is set to tagged:
 - (a) Frames sent from the End User that do not have 802.1q tags will be discarded;

Broadband Anchor Service Description—continued

- (b) Tagged traffic sent from the End User or Service Provider are treated as follows:
 - (i) Frames tagged with PCP = 5 will be treated as High Traffic Class.
 - (ii) Frames tagged with PCP = 0 will be treated as Low Traffic Class.
 - (iii) Frames tagged with PCP = 1, 2, 3, 4, 6, or 7 will be remarked as PCP 0 and treated as Low Traffic Class.
 - (iv) Frames will be treated as follows:

| Туре | Ingress | Transport |
|--------------------|-------------------------------------|--|
| Low Traffic Class | $CIR \ge 0$ | Queued and weighted fairly |
| | $EIR \ge 0$ | under congestion conditions |
| | Policed at ingress based on CBS/EBS | Frames classified as EIR dropped first |
| High Traffic Class | $CIR \ge 0$ | Strictly prioritised |
| | $EIR \ge 0$ | |
| | Policed at ingress based on CBS | |

- (v) Downstream traffic class is determined using the s-tag PCP setting although it is recommended that both the s-tag and c-tag is set to the same value.
- 3.7.5 The following Service Template is available for the Bitstream 2 Accelerate Service consisting of a Baseband Service with one instance of the ATA Voice Service and one Ethernet Access-EVPL Bitstream service as follows:

| Template | | | Evolve 100-20-2.5-2.5 |
|-----------------------|------------------------|------|-----------------------|
| ATA ports | | | 1 |
| Headline ² | Low Traffic Class | Down | 100 |
| | (Mbps) | Up | 20 |
| | High Traffic Class | Down | 2.5 |
| | (Mbps) | Up | 2.5 |
| Low Traffic Class P | IR (Mbps) ³ | Down | 110 |
| | | Up | 22 |
| Low Traffic Class | EIR | Mbps | 107.5 |
| Downstream | EBS | kB | 180 |
| | CIR | Mbps | 2.5 |
| | CBS | kB | 32 |
| Low Traffic Class | EIR | Mbps | 19.5 |
| Upstream | EBS | kB | 100 |
| | CIR | Mbps | 2.5 |
| | CBS | kB | 32 |
| | | | |

| in menor service Description commune | | | |
|--------------------------------------|-----|------|---|
| Template | | | Evolve 100-20-2.5-2.5 ¹ |
| High Traffic Class | EIR | Mbps | 0 |
| Downstream | EBS | kB | 0 |
| | CIR | Mbps | 2.5 |
| | CBS | kB | 32 |
| High Traffic Class | EIR | Mbps | 0 |
| Upstream | EBS | kB | 0 |
| | CIR | Mbps | 2.5 |
| | CBS | kB | 32 |
| | | | |

Broadband Anchor Service Description—continued

¹Available for residential connections only.

²Available for residential connections only. The headline rate is the Layer 2 bandwidth prior to the addition of the overhead described in clause 3.6.2.

³Low Traffic Class "Peak Information Rate" is the headline rate plus the bandwidth overhead described in clause 3.6.2.

UNI – NNI characteristics

- 3.7.6 All Bitstream 2 Accelerate Services (ATA Voice and Access-EVPL) on an ONT must belong to the same Service Provider and must each connect to an E-NNI belonging to that Service Provider. However each Service can connect to a different E-NNI at the same or different POI within a Coverage Area.
- 3.7.7 The sum of High and Low Traffic Class traffic profiles of all services delivered at a UFB Handover Connection Service can exceed the UFB Handover Connection Service line rate. If there is insufficient line rate to deliver the traffic then frames will be randomly discarded, based on their Class of Service precedence, and Service Levels for that Class of Service do not apply. It is therefore the Service Provider's responsibility to shape and queue traffic appropriately.

Omit clauses 3.8 to 3.11.

In clause 3.17.4, delete "or Service Provider Premises or NBAP (as applicable)".

In clause 4, delete "or Service Provider Premises or NBAP (as applicable)" in each place.

In clause 5.1, replace "E-AVPL" with "Access-EVPL".

In clause 7.1, delete ", Service Providers Premises or NBAP (as applicable)".

Replace clause 7.2 with:

7.2 A diverse lead-in between the Fibre Access Point and the Premises may be available as an option for some but not all Premises. Standard Installation Charges and Service Levels do not apply to the provision of the diverse products that involve diverse access to the End User Premises. Each instance of the Bitstream 2 Accelerate Service, primary and diverse, will be treated as an individual line for the purpose of availability Service Levels.

In Appendix A,—

Broadband Anchor Service Description—continued

- (a) in the second bullet, replace "only apply to" with "only apply from the"; and
- (b) after the third bullet, insert:
 - The Bitstream 2 Accelerate Service Template contains a single Access-EVPL and one (optional) Voice-EVPL, which is part of the Baseband Service Description. The Access-EVPL and Voice-EVPL OVC must belong to the same Service Provider, but can be managed to the same or different E-NNIs.
- (c) delete "The Bitstream services support simultaneous delivery of multiple Service Templates from the same or multiple Service Providers as follows:"; and
- (d) delete the last 5 bullets.

In Appendix B, replace the first 2 rows of the table (labelled "Ethernet" and "UNI") with:

| Ethernet | Ethernet II or 802.3 untagged interface; or |
|----------|--|
| | 802.1q tagged interface with |
| | • VLAN id = 10 |
| | Untagged (Low Traffic Class) |
| | • 802.1p = 0, 1, 2, 3, 4, 6, 7 (Low Traffic Class) |
| | • 802.1p = 5 (High Traffic Class) |
| UNI | ONT supports: |
| | • 4 x 100/1000Base-T UNI |
| | • 1 or 2 x ATA Voice ports |
| | Optional additional ports: |
| | • WiFi |

In Appendix B, in row 4 of the table (labelled "VLAN"), replace "E-AVPL" with "Access-EVPL".

In Appendix B, in row 7 of the table (labelled "Optic Path"), replace "Laser types" with "Optical".

Voice Anchor Service Description

Replace clause 1.3 with:

1.3 This Service Description describes the Baseband Service where it is delivered using GPON Fibre access.

Replace clause 2 with:

2 The Baseband Service

- 2.1 The Baseband Service is a service to enable the delivery of PSTN-grade analogue phone and telephony services over a GPON point-to-multipoint Fibre access from the End User Site to the Handover Point.
- 2.2 A diagram of the configuration for Baseband Service is set out in Appendix A. The Baseband Service delivers an analogue voice service from an ATA port on

Voice Anchor Service Description—continued

the ONT located at the End User Premises to the UFB Handover Connection Service located at the POI that enables a Service Provider to interconnect with the LFC Network.

- 2.3 The Baseband Service is an input service which a Service Provider can combine with other LFC services (or with the Service Provider's own network or wholesale services provided by other service providers) to provide fibre based voice telecommunications services to End Users.
- 2.4 The Baseband Service has the following key characteristics:
 - 2.4.1 Supports PSTN-compatible analogue telephony devices connected to an ATA Port on the ONT. Facsimile and dialup modem support may be limited, and such limitations will grow over time. The LFC will advise the Service Provider of these limitations from time to time.
 - 2.4.2 Uses a carrier-grade G.711a/G.711u Voice Codec with a packetisation rate of 10ms.
 - 2.4.3 Supports SIP signalling.
 - 2.4.4 Delivered as a bitstream service per ONT to a UFB Handover Connection Service located at a POI using a dedicated Voice Ethernet Virtual Private Line Operator Virtual Circuit (Voice-EVPL OVC) VoIP bitstream service.
 - 2.4.5 Supports New Zealand PSTN tones and cadences as set out in Telecom Network Advisory Specification TNA 102.
 - 2.4.6 Includes a facility to allow Service Providers to remotely configure and manage the service:
 - 2.4.7 Can be delivered as "voice-only", or as part of the Bitstream 2 Accelerate Service.

Replace clause 3.1 with:

3.1 The Baseband Service will be made available during the installation of a "voice-only" service, or as part of a Bitstream 2 Accelerate service, each of which includes a Standard Install¹ as set out in the Operations Manual. The LFC will provide Non-Standard Installs as an ancillary service. To avoid doubt, a Standard Install does not include the connection of the Baseband Service into the Premises wiring.

In clause 3.3, after "Operations Manual." insert "The testing may be limited to an outgoing call and is subject to the Service Provider having configured the voice service at time of install."

In clause 3.4,—

¹ Standard Install parameters may differ between LFCs

Voice Anchor Service Description—continued

- (a) in paragraph (a), delete subparagraphs (ii) and (iii); and
- (b) replace "Items (a) and (b) are" with "Item (a) is".

Replace clauses 3.5 to 3.7 with:

- 3.5 The Baseband Service provides the following key service attributes:
 - 3.5.1 One or more RJ11 ATA interfaces on the ONT located at the End User Premises, which converts analogue voice to VoIP frames upstream, and VoIP frames to analogue voice downstream.
 - 3.5.2 A single SIP User Agent in the ONT, which acts as a logical network end point and manages the Voice sessions using SIP protocols.
 - 3.5.3 An Access-EVPL that associates the SIP User Agent in the ONT with an E-NNI. The Access-EVPL UNI is internal to the ONT and is not accessible externally.
 - 3.5.4 Delivered at the Handover Point as a G.711a/G.711u bitstream with SIP signalling over a single 802.1ad SVLAN on the ENNI.
 - 3.5.5 RGW Voice traffic will be treated as High Traffic Class.
 - 3.5.6 Supports the voice standards set out in clause 9.2 of the General Terms.
- 3.6 The Baseband Service supports:
- 3.6.1 Analogue voice;
- 3.6.2 Facsimile; and
- 3.6.3 A minimum of 14.4 kbps modem transmission,

but it may not be backwards compatible with all existing facsimilies, and modems and customer premises equipment (CPE).

- 3.7 The Baseband Service may be ordered by the Service Provider in one of the following combinations:
- 3.7.1 the Baseband Service on its own, suitable for a voice-only service; or
- 3.7.2 in conjunction with the Bitstream 2 Accelerate Service Template that combines Baseband with the Bitstream Service defined in the Bitstream 2 Accelerate Service Description.

Omit clauses 3.8 to 3.10.

Replace clause 3.13.3 with:

- 3.13.3 a facility to allow Service Providers to remotely configure and manage the Baseband Service; and
- 3.13.4 a tool to assist the Service Provider in determining the location and availability of the Baseband Service (pre-qualification).

Replace clause 3.14.2(a) with:

Voice Anchor Service Description—continued

 (a) beyond the Service Demarcation Points. To avoid doubt, the Baseband Service does not include the connection of the ATA port on the ONT into the Premises wiring;

In clause 3.14.4, delete ", Service Providers Premises or NBAP (as applicable)".

In the heading to clause 4, delete ", Service Providers Premises or NBAP (as applicable)".

Replace clause 4.1 with:

4.1 The Service Demarcation Point at the End User Premises is the RJ11 port on the ONT.

In clause 4.2, delete ", Service Providers Premises or NBAP (as applicable)" in each place.

Replace clause 5.1 with:

5.1 The Baseband Service is delivered as a single VLAN (the logical Service Demarcation Point) on the UFB Handover Connection Service located at the POI.

In Appendix A,—

- (a) in the first bullet, delete ", i.e. there is no incremental charge from the Intermediate POI to the POI"; and
- (b) delete the second and third bullets; and
- (c) after the fourth bullet (relating to service levels), insert:
 - The Voice-EVPL is used to describe the combination of ATA Port, SIP User Agent and associated Access-EVPL OVC to the E-NNI.
- (d) delete "The Bitstream services support simultaneous delivery of multiple Service Templates from the same or multiple Service Providers as follows:"; and
- (e) delete the last 4 bullets.

Replace Appendix B with:

Appendix B: Technical Specification

Technical Specification

| RJ11 |
|--|
| Analogue interface compliant with PTC 220, section 5 |
| |
| 802.1ad VLAN or double-tagged QnQ |
| PCP = 45 |
| |
| DTMF dialling |
| |

| | The wavelengths of 1625 nm and 1650nm are reserved for network maintenance testing purposes, (live GPON network) compliant with ITU-T L.41. |
|-------------------------|---|
| Optical Path Performace | Communal Network performance |
| | Total GPON insertion Loss OLT to ONT design target is $= \le 27.0$ db (28.5db $- 1.5$ db) Optical Fibre Attenuation Co-Efficient (L) (ITU-T G.652. & G657.A) = |
| | ≤ 0.4 db/km Splice Loss (S) = ≤ 0.15 db |

Voice Anchor Service Description—continued

| Mated Connector loss (C) = ≤ 0.3 db |
|---|
| Mated Connector Reflection = \geq 55db |
| Total Insertion Loss of network (IL) is calculated from $IL = 0.4L + 0.15S + 0.3C$ (excluding PON splitter) |
| Splitter performance |
| $1:32 = \le 17 db$ |
| $1:16 = \le 14$ db |
| $1:8 = \le 11 db$ |
| $1:4 = \le 7.3 db$ |
| 1:2 = < 4.0db |

Large-User DFAS Service Description

Replace clause 8.2 with:

8.2 Diversity (a second or subsequent instance of the Direct Fibre Access Service between the End User Premises, Service Provider Premises or NBAP (as applicable) and the LFC's relevant Central Office) may be available on request. Standard Installation Charges and Service Levels do not apply to the provision of diversity products and additional charges may apply where diversity is available.

Omit clauses 8.4 and 8.5.

In Appendix B, in row 3 of the table (labelled "Optic Path"), replace "Laser types" with "Optical".

Technical standards cited in service descriptions

rr 9, 12, 16

Part 1

Broadband Anchor Service Description

| Abbreviation used in service description | Full title |
|--|--|
| IEC 61754-4 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 4: Type SC connector family (2013) |
| IEC 61754-20 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 20: Type LC connector family (2012) |
| ND0556 | Optical Fibre – Layer 1 Network Test Plan – Volumes 1-3 (December 2016) |
| ITU-T G.652 | Characteristics of a single-mode optical fibre and cable (November 2016) |
| ITU-T G.657 | Characteristics of a bending-loss insensitive single-mode optical fibre and cable (November 2016) |
| ITU-T G.984 | ITU-T G.984 Umbrella Standard (2010) |
| IEEE 802.3 | IEEE Standard for Ethernet (2018) |
| ITU-T L.41 | Maintenance wavelength on fibres carrying signals (May 2000) |
| | |

Part 2

Voice Anchor Service Description

| Abbreviation used in service description | Full title |
|---|--|
| IEC 61754-4 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 4: Type SC connector family (2013) |
| IEC 61754-20 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 20: Type LC connector family (2012) |
| ND0556 | Optical Fibre – Layer 1 Network Test Plan – Volumes 1-3 (December 2016) |
| ITU-T G.652 | Characteristics of a single-mode optical fibre and cable (November 2016) |
| ITU-T G.657 | Characteristics of a bending-loss insensitive single-mode optical fibre and cable (November 2016) |
| ITU-T G.711a/G.711u | ITU-T G.711 Pulse code modulation (PCM) of voice frequencies (2000) |
| ITU-T G.984 | ITU-T G.984 Umbrella Standard (2010) |
| IEEE 802.3 | IEEE Standard for Ethernet (2018) |
| ITU-T L.41 | Maintenance wavelength on fibres carrying signals (May 2000) |
| TNA 102 | Characteristics of the Spark Analogue Telephone Network Customer Interface (August 2019) |
| RFC 2833 | RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals (December 2006) |
| RFC 3261 | SIP: Session Initiation Protocol (June 2002) |
| PTC 220 | Requirements for Private Voice Networks connected to the PSTN/ISDN/ VoIP public networks (July 2019) |

Part 3 Large-User DFAS Service Description

| Abbreviation used in | |
|----------------------|--|
| service description | Full title |
| IEC 61754-4 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 4: Type SC connector family (2013) |
| IEC 61754-20 | Fibre optic interconnecting devices and passive components – Fibre optic connector interfaces – Part 20: Type LC connector family (2012) |
| ND0556 | Optical Fibre – Layer 1 Network Test Plan – Volumes 1-3 (December 2016) |
| ITU-T G.652 | Characteristics of a single-mode optical fibre and cable (November 2016) |
| ITU-T G.657 | Characteristics of a bending-loss insensitive single-mode optical fibre and cable (November 2016) |
| ITU-T G.984 | ITU-T G.984 Umbrella Standard (2010) |
| IEEE 802.3 | IEEE Standard for Ethernet (2018) |
| ITU-T L.41 | Maintenance wavelength on fibres carrying signals (May 2000) |

Clerk of the Executive Council.

Explanatory note

This note is not part of the regulations, but is intended to indicate their general effect. [TBC]

Issued under the authority of the Legislation Act 2012. Date of notification in *Gazette*: These regulations are administered by the Ministry of Business, Innovation, and Employment.