

Review of CCUS/CCS Potential in New Zealand

Written in support of the Gas Transition Plan

Prepared for Gas Industry Company

Prepared by Wood Beca Limited

28 March 2023



Contents

Executive Summary	2
1 Context	4
1.1 Wood Beca – Gas Industry Company agreed SoW	4
1.2 Overview of CCUS and CCS	5
1.3 Carbon capture and storage	6
1.4 Carbon capture, utilisation and storage – Taranaki concepts	7
1.5 Research rationale	9
1.6 Agreed terms of confidentiality	10
2 Security of Natural Gas Supply	11
3 Carbon Capture Quantities	12
4 OMV (NZ) Ltd	14
4.1 Base Case – offshore CO ₂ stripping and injection	14
4.2 Technical considerations	14
5 Todd Energy	15
5.1 Base Case – Kapuni CCS	15
5.2 Technical considerations	15
6 Class 5 Cost Estimations	15
6.1 Overall cost of CCS in New Zealand (onshore and offshore)	15
6.2 Implication with ETS	21
7 Additional Considerations	22
7.1 A CO ₂ economy	22
8 Concluding Remarks and Recommendations	23
8.1 Is CCS technically and economically viable in New Zealand?	23
8.2 What contribution can sequestration make to emissions reductions, security of supply and energy affordability?	23
8.3 How does a pathway that includes sequestration compares to alternative scenarios that do not?	24
9 References	24

Figures

Figure 1-1. Flow diagram of ERP and CCUS/CCS applicability.....	4
Figure 1-2. Diagram of CCUS / CCS.....	5
Figure 1-3. Taranaki region CCUS/CCS possible participants.....	6
Figure 1-4. Global CCUS/CCS projects as of 2022 (Global CCS Institute, 2022)	6

Figure 1-5. Statistical distribution of global CCS projects (Global CCS Institute, 2022)	7
Figure 1-6. Methanol block flow diagram.....	8
Figure 1-7. Maui & Kapuni locations.....	10
Figure 2-1. Historical production (MBIE data) across currently operated OMV and Todd assets (Data sourced from MBIE, 2021b).....	11
Figure 2-2. Maui and Kapuni non-hydrocarbon bearing void space referenced in Billion Cubic Feet (BCF). Data sourced from MBIE, 2021b.	12
Figure 3-1. Cumulative CO ₂ production profile for Maui East and Kapuni fields.....	14
Figure 3-2. Emission reduction budgets – pathway with and without CCS.....	14
Figure 6-1. Scaled CO ₂ capture cost (OOM), 2022 basis	18
Figure 6-2. Scaled CO ₂ compression cost (OOM), 2022 basis.....	19
Figure 6-3. Onshore pipeline cost (OOM), 132 bar design pressure, dense phase pipeline graph and line size guidance (40km 120 bar dense phase pipeline)	19
Figure 6-4. Offshore pipeline cost (OOM), 144 bar design pressure, dense phase pipeline graph and line size guidance (40km 120 bar dense phase pipeline)	20
Figure 6-5. ETS draft advice and forecast curve (box plot represents Class 5 cost estimates for CCS facilities of 0.2 – 1.2 Mtpa capacity, 0.5 – 40 km pipeline length and 20 year field life).....	22

Table of Tables

Table 7-1 Summary table for onshore CCS scenario - 1 Mtpa capacity, 1 km pipeline, 20 year field life	16
Table 7-2 Q4 2022 average exchange rates (OFX, 2022)	17
Table 7-3 Onshore CCS Class 5 cost estimates: variation and impact on cost (+30% contingency applied on overall whole scope TIC n+1 well philosophy, 0.5 Mtpa capacity per well assumption)	21

Appendices

- Appendices 1. Not included in this report – Wood Beca OMV CCUS Technical Review
- Appendices 2. Not included in this report – Wood Beca Todd CCUS Technical Review
- Appendices 3. Provided separately – Cost Analysis

Revision History

Revision N°	Prepared By	Description	Date
A	Wood Beca Ltd	Draft for Operator review	25/01/2023
B	Wood Beca Ltd	Draft for client review (revised based on comments from Operators)	13/03/2023
C	Wood Beca Ltd	Issued as final	28/03/2023

Document Acceptance

Action	Name	Signed	Date
Prepared by	Elizabeth Timings		28/03/2023
Reviewed by	Nick Cozens	NWJC	28/03/2023
Approved by	Phil Robson		28/03/2023
on behalf of	Wood Beca Limited		

© WoodBeca Ltd (WoodBeca) 2023 (unless WoodBeca has expressly agreed otherwise with the Client in writing).

This report has been prepared by WoodBeca on the specific instructions of our Client. It is solely for our Client's use for the purpose for which it is intended in accordance with the agreed scope of work. Any use or reliance by any person contrary to the above, to which WoodBeca has not given its prior written consent, is at that person's own risk.

List of Abbreviations

2C – Proven and probable reserves

2P – Best estimate of contingent resources

APAC – Asia Pacific And China

BCF – Billion Cubic Feet of Gas. For context:

- 1) Maui GIIP ~ 4000BCF, or
- 2) Calendar year 2021 New Zealand total gas production was 139BCF

CAPEX – Capital Expenditure

CO₂ – Carbon Dioxide

CCS – Carbon Capture and Storage

CCUS – Carbon Capture, Utilisation and Storage

EOR - Enhanced Oil Recovery

ERB – Emission Reduction Budget

ETS – Emission Trading Scheme

FEED – Front End Engineering Design

GIIP – Gas Initially In Place

LTS – Low Temperature Separation

Mtpa – Million Tonnes per Annum

OOM – Order of Magnitude

OPEX – Operating Expenditure Costs

RKM – Rimu/Kauri/Manutahi

TAWN – Tariki/Ahuroa/Waihapa/Ngaere

TCF – Trillion Cubic Feet

TIC – Total Installed Costs. For context this includes:

- 1) CO₂ Capture (NZD/tonne)
- 2) CO₂ Transportation (NZD/tonne/km)
- 3) CO₂ Injection (NZD/tonne)

Executive Summary

Globally, emission reduction targets are being pursued through various decarbonising initiatives; displacement of fossil fuel with renewable alternatives being both significant and challenging. However, energy transition will be gradual, occurring over many decades and only, when affordable and reliable alternatives are sourced, and developed. Demand for oil and natural gas continue, not only in New Zealand, but globally, as demand growth persists (McKinsey & Company, 2022).

In the context of New Zealand, objectives set out under the Gas Transition Plan seek a series of recommendations, which relate to the possible role CCUS and CCS could play to meet emission reduction targets, specifically:

- Whether the technology is technically and economically viable in New Zealand
- What contribution sequestration can make to emissions reductions, security of supply and energy affordability
- How a pathway that includes sequestration compares to alternative scenarios
- The requirement for a legislative framework to enable CCS and CCUS

Wood Beca have reviewed CCUS/CCS opportunities and report on two potential CCS candidates reviewing the technical and economic aspects of these projects only - The Maui and Kapuni gas fields in Taranaki. These are late life assets now reaching depletion which, alternatively serve as technically feasible candidates, to store decadal scale volumes of CO₂ and potentially contributing towards emission reduction objectives. While CCS and CCUS initiatives are cited in this report, they remain subject to technology advancement, consenting processes, economic, environmental assessments and supportive legislation.

Emissions associated with natural gas production currently (2021) account for ~ 0.715 Mtpa CO₂ – across all production in Taranaki. The Operators are targeting a 2027 implementation, subject to normal project lifecycle process (business case, regulatory environment, consenting), application of CCS at Maui East (step out discovery from the Maui A platform) and Kapuni, has the potential effect on ERB 2 and 3 as described below:

- ERB 2 (2026 – 2030) target annual average is 61Mt. This is an 11.5 Mt reduction from ERB 1 (target annual average of 72.5 Mt CO₂ during 2022 – 2025).
 - Kapuni follows forecast 2P production profiles; natural gas supply declining steadily out to 2048. This would produce 0.75 Mt of CO₂ during the 2027–2030 period. Should Maui East commence operations by 2027, up to 1.36 Mt CO₂ would be produced during the 2027-2030 period. Together, 2.1 Mt CO₂ could be sequestered from Maui East and Kapuni.
- ERB 3 (2031 – 2035) target annual average is 48 Mt. This is an 13Mt reduction from ERB 2.
 - Kapuni follows forecast 2P production profiles; natural gas supply declining steadily out to 2048. This would produce 0.56 Mt CO₂ would be produced during the 2031–2035 period. Should Maui East commence operations by 2027, up to 1.7 Mt of CO₂ could be produced during the 2031-2035 period. Together, 2.3 Mt CO₂ could be sequestered from Maui East and Kapuni.

Between 2027 and 2035, a sum total of 4.4 Mt of emissions associated with natural gas production could be sequestered through CCS activity.

Class 5 (-50%/+100%) cost estimates, based on international norms for onshore application of CCS at natural gas production facilities in New Zealand range in the order of \$30 – 110 NZD/tonne CO₂. While actual values are highly dependent on site specifics, this range provides alternatives to current ETS forecasts facing natural gas producers.

Considering the wider concepts of CCUS, CO₂ is a commodity growing in global importance. In the Taranaki region, CO₂ is an important chemical building block in the production of urea and methanol – two large industrial outputs in the region. These industries are highly reliant on CO₂ rich natural gas (consuming over 50% of produced natural gas in New Zealand). The Kapuni – Methanex low temperature separation pipeline will be an important asset to consider as a transport vector for CO₂ producers, CO₂ off takers and those proximal to potential CO₂ sinks (e.g. the RKM, and Pohokura fields). Further, as emerging CCS technologies mature, additional emission reduction initiatives such as direct air carbon capture may benefit from lower barriers to commercialisation.

1 Context

The purpose of this study is to provide inputs to the Gas Transition Plan on how CCS and CCUS may contribute to emissions reduction for New Zealand. The scope of this report was to focus on the technical and economic feasibility of CCS and CCUS. This report does not cover the significant legislative or consenting aspects of the pathway to implementation for CCS or CCUS and recognition of it as a viable carbon sequestration mechanism in New Zealand.




Figure 1-1. Flow diagram of ERP and CCUS/CCS applicability

Pillar I of the Gas Transition Plan focuses on articulating transition pathways for the fossil fuel sector whereas Pillar II focuses on potential decarbonisation solutions, including renewable gases and CCS/CCUS. This review therefore focusses on Pillar II.

Gas Industry Company seeks:

- Whether the technology is technically and economically viable in New Zealand
- The potential volume of CO₂ that may be sequestered
- How a pathway that includes sequestration compares to alternative scenarios

1.1 Wood Beca – Gas Industry Company agreed SoW

Agreed terms of non-disclosure restrict the level of detail this report can publish. As Wood Beca hold confidentiality agreements with the Operators – and not Gas Industry Company. The primary role of Wood Beca is to act as the technical intermediary between Gas Industry Company and – in this instance Operators, OMV and Todd. Specifically, Wood Beca will seek to:

- Determine the contribution CCS *could* provide to ongoing security of supply and energy affordability.
- Review Maui and Kapuni technical considerations as possible CCS candidates.
- Provide Class 5 (-50% / + 100%) cost considerations for successful CCS implication.
- Quantify the role CCS could make on an annual basis utilising the operator data
- Describe how a pathway that includes CCS compares to alternative scenarios that do not.

To note – Wood Beca have not conducted a subsurface review of reservoir candidates. This remains the preserve of the Operators.

Wood Beca do note the following steps have been taken to ensure integrity of our review:

- November 23rd – Wood Beca / OMV technical workshop.
- December 14th – Wood Beca / Todd technical workshop.

Consequently, Wood Beca have generated three technical review reports titled:

Appendices 1. Not included in this report – Wood Beca OMV CCUS Technical Review

Appendices 2. Not included in this report – Wood Beca Todd CCUS Technical Review

Appendices 3. Provided separately – Cost Analysis

Should Gas Industry Company wish to access these outputs, this will occur under separate confidentiality arrangements between the Operators and Gas Industry Company.

1.2 Overview of CCUS and CCS

CCUS and CCS refer to the process of capturing CO₂ and either storing it permanently (CCS) or utilising it by converting it into valuable products, such as fuels and chemicals (CCUS). Both CCUS and CCS are based on carbon capture, the difference between the two lies in what happens after the capture step (Figure 1-2).




Figure 1-2. Diagram of CCUS / CCS

Candidates in the carbon capture economy, known to be investigating CCUS and CCS initiatives in New Zealand are upstream oil and gas and midstream chemical companies. Oil and gas companies, OMV and Todd, are currently investigating CCS research, while chemical manufacturing companies Ballance Agri-Nutrients Ltd (Ballance) and Methanex New Zealand Ltd (Methanex) are potential CCUS candidates subject to the right legislative framework, product demand requirements and commercial frameworks, therefore considered agnostic now (Figure 1-3).




Figure 1-3. Taranaki region CCUS/CCS possible participants

1.3 Carbon capture and storage

According to the Global CCS Institute 2022 Status Report (Global CCS Institute, 2022), over 40 MtCO₂ is captured annually and a further 200 MtCO₂ capture is in development (Figure 1-4).




Figure 1-4. Global CCUS/CCS projects as of 2022 (Global CCS Institute, 2022)

Further review of this data (Figure 1-5) reveals a number of insights:

- The mean value of CCS/CCUS projects in the APAC region is 2 Mtpa, which is significantly larger than the global mean. Over 90% of APAC projects are >1 Mtpa, with 4 projects >4 Mtpa. The size of these projects indicates the shift towards large CCUS hubs rather than smaller individual facilities in the APAC region, servicing industrial clusters with multiple emitters accessing a common storage site.
- Globally, both EOR and permanent CCS projects have successfully been deployed in a number of jurisdictions, mostly onshore with a small number occurring offshore. Of the ~ 200 projects cited:
 - 58% are permanent **CCS** projects,
 - 16% are EOR projects,
 - 26% of projects are various use or undefined.
- The mean size of global CCS projects is 0.5 Mtpa, slightly lower than the average size of global EOR projects (0.8 Mtpa).

OMV and Todd represent potential candidates for CCS in New Zealand. Emissions associated with OMV's potential Maui East development (>0.34 Mtpa) represent a capacity lower than the global mean of permanent CCS projects. If Todd's existing Kapuni gas field operates at current capacity, Kapuni's

associated emissions would represent a capacity similar to the global mean of permanent CCS projects (Figure 1-5).




Figure 1-5. Statistical distribution of global CCS projects (Global CCS Institute, 2022)

1.4 Carbon capture, utilisation and storage – Taranaki concepts

There is currently a shortage of industrial grade CO₂ in New Zealand. In Taranaki, there are two large chemical production facilities which rely on a CO₂ feedstock provided through a reliable supply of natural gas.

1.4.1 Methanex

Methanex, which is a major industrial participant in the Taranaki region, is also an active CCUS participant in North America. The chemical reactions involved in making methanol lead to the production of excess H₂ (Figure 1-6). By injecting additional CO₂ to combine with the excess hydrogen, higher methanol yields and increased production efficiency can be expected than the current natural gas (pre combustion) feed.

Conceivably, the current Kapuni LTS 070 pipeline infrastructure, which runs from Kapuni to Methanex can carry 22TJ/day, transporting in the order of 0.1Mtpa CO₂. It is conceivable that this pipeline could transport concentrated CO₂, this would need to be confirmed by an engineering assessment. A successful example of CCUS at Methanex is, in 2013 Methanex modified its North American Medicine Hat plant and began to introduce CO₂ sourced from an industrial neighbour into its production process, utilising approximately 0.08 Mtpa CO₂ in 2021 (Methanex, 2021).




Figure 1-6. Methanol block flow diagram

1.4.2 Ballance Agri - Nutrients Ltd, Kapuni site

The Ballance Agri-Nutrients (Ballance) ammonia-urea manufacturing plant is also located near the Kapuni – Methanex LTS pipeline and the Kapuni gas field. Production of ammonia-urea at this site contributes approx. total annual emissions of 0.22 Mt. Close to 0.18 Mt of which, are from the reforming process, this varies based on annual production (Beca, 2023).

1.4.3 Other concepts

Other CCS concepts, albeit at much lower technical readiness levels than methanol or urea chemical production, include Direct Air Carbon Capture (DAC) and chemical leaching of olivine. Two such initiatives are under consideration in New Zealand by private start-ups.

Aspiring Materials. <https://www.aspiringmaterials.com/>

- Acid is used to dissolve olivine, a mineral found in serpentine group minerals, pyroxenes, and amphiboles. These minerals are abundantly found in the earth's crust.
- A solution rich in dissolved silica, iron and magnesium is yielded.
 - The magnesium component being particularly attractive and useful for atmospheric CO₂ absorption, producing magnesium hydroxide (Scott et al., 2021).

Capture6. <https://capture6.org/>

- Capture6 claims - at a cost of less than \$100 USD per tonne of CO₂ (Capture6, 2022), successful application of its proprietary technology could lead to gigaton scale removal goals.
- Capture6 claims a novel re-organization of existing chemical elements and available technology, its DAC process converts CO₂ to calcium carbonate (lime).

While CO₂ is ultimately utilised, it is the by-products of these processes that carry additional value and opportunity.

1.5 Research rationale

Directly supporting Pillar II objectives, this review focusses *primarily* on CCS (and not CCUS) application in the Taranaki region for the following salient reasons:

- CCS technology is available and commercially in use in several countries.
- Commencing in 2022 and concluding in 2035, the sum total of the three required ERB's amount to ~ 31 Mt of total CO₂ reduction (Ministry for the Environment, 2022a). Should natural gas production levels be maintained at current contracted rates over the same period of time, then emissions from Kapuni (~8.5 Mt) and possibly Maui East (~4.5 Mt) will equate to ~12 Mt. The role CCS could therefore play in emission reductions associated with natural gas production is significant.

- Global examples provide evidence of successful CCS application at natural gas production facilities.
- Reservoir void space, no longer hydrocarbon bearing, at late life assets Maui and Kapuni, represent depleted theoretical volume in the order of 5 TCF – a volume sufficient to accommodate several decades of introduced CO₂.
- In the fullness of time, adopted CCS practise may support a wider CCUS carbon economy concept. Fuel and chemical production, horticulture, or food and beverage utilisation, may all be benefactors of a CO₂ contribution and withdrawal network (Section 8.1).

1.6 Agreed terms of confidentiality

Wood Beca has, under mutually agreed terms of confidentiality, received data from OMV and Todd. The nature of this data transfer relates to CCS candidates Maui (OMV) and Kapuni (Todd).




Figure 1-7. Maui & Kapuni locations

In the broadest terms, data transferred to Wood Beca relates to the following:

- Means to determine processing emissions associated with the current and possible operations at both Maui and Kapuni.
- Concept assessment for potential CCS development scenarios. Only base case scenarios will be referenced in this report.
- Targeted sequestration volumes at both Maui and Kapuni fields.

2 Security of Natural Gas Supply

Presently, circa 53% of New Zealand's *primary* energy comes from natural gas (21%) and oil (32%) (MBIE, 2021a).. While projections indicate (a steady decline in natural gas usage out to 2050 (Concept Consulting, 2022), the effect higher carbon prices will have on this supply and therefore demand remains unclear.

Meeting current demand, operators are actively researching technical and commercial merits of CCS activities in Taranaki, in part to 1) relieve their ETS liabilities, 2) meet their stated carbon reduction measures, and 3) provide additional production options to ensure affordable supply is met.

Close to ~70% of natural gas demand is being met by aging fields (**OMV** – Maui, Pohokura, **Todd** – Kapuni, Mangahewa, McKee) (MBIE, 2021b). Cumulative deliverability from these assets, in recent years is plateauing (Figure 2-1), placing upward pressure on natural gas price and assurance of continued supply.




Figure 2-1. Historical production (MBIE data) across currently operated OMV and Todd assets (Data sourced from MBIE, 2021b).

Analysing statutory reporting and reviewing recent exploratory drilling results (shared under NDA between OMV and Wood Beca), several important insights are revealed:

Statutory reporting and corresponding observations:

- Maui and Kapuni natural gas delivery, has for the past 10 years, been reasonably steady, albeit down from 2003. Pohokura and Mangahewa fields continue to be large producers alongside the older Maui and Kapuni volumes.
- End of field life forecasts at Maui and Kapuni, *currently* occur before large scale electrification alternatives conceivably take effect e.g. Transpower electricity supply/demand forecasts (Transpower, 2022), which may present primary energy supply issues.
- Remaining (2P) reserves at Maui and Kapuni respectively indicate 7% and 14% of ultimate reserve remains (Figure 2-1). The inference being, produced volumes represent a theoretical void space of >5 TCF, where introduced CO₂ could be re-injected.

- Notwithstanding (2C) contingent resource values may increase remaining available natural gas volumes still to be produced, this data remains confidential to the Operators and has not been pursued in this report.
 - It should be noted, (2C) resource interpretations range from 0.8 to > 1.2 TCF at Kapuni, and 250 – 300 BCF at Maui (MBIE, 2021b).




Figure 2-2. Maui and Kapuni non-hydrocarbon bearing void space referenced in Billion Cubic Feet (BCF). Data sourced from MBIE, 2021b.

Confidential data and corresponding observations:

- During Q4 2021, Maui East-1 was successfully drilled at the end of the Maui-A Crestal Infill drilling campaign. Discovered was a resource estimate 180 – 280 BCF (MBIE, 2021b) comprising elevated in place CO₂ volumes. Commencing in Q4 2022 – Q1 2023, this discovery will be appraised to confirm volumes and CO₂ disposal solutions.
- Should this discovery confirm a reserves upgrade, current and possible Maui East production forecast to 2039 is a foreseeable scenario, subject to factors highlighted in the Executive Summary. However, securing access to this natural gas volume will also attract up to 90 BCF (~4.5 Mt) CO₂ over its production life.
- Data supplied by Todd (confidential) has allowed Wood Beca to conclude the Kapuni field exhibits all necessary components to support a functioning CCS facility.

3 Carbon Capture Quantities

An output of this report is to provide commentary on the role CCUS and CCS may have on emissions reductions.

Emissions associated with natural gas production, predominately flaring and venting activities, currently account for 0.715 Mtpa (Ministry for the Environment, 2022b). Significantly:

- Kapuni operations contribute most of these emissions (currently 2 production trains, which emit >0.5 Mtpa CO₂ at capacity). At full plant capacity with 3 trains operating, Kapuni could contribute up to ~0.72 Mtpa of CO₂. For every PJ of natural gas extracted from the Kapuni field, ~13 kt of CO₂ is currently produced.
- Potential emissions from a Maui East development are expected to add at least 0.34 Mtpa. Every PJ of natural gas from the Maui East is expected to have an associated ~10 kt CO₂.

Combined CO₂ capacity of storage at Maui East (>0.34 Mtpa) and Kapuni (0.72 Mtpa) future operations equate to anecdotal values in the order of 1.06Mtpa. However, correlating future emissions at Kapuni to publicly available 2P production profiles, which steadily decline out to 2048, emissions are expected to decline (Figure 3-1). Based on the Operators expected project development timeframes, subject to suitable CO₂ disposal solutions being identified and sanctioned, CCS activities at both Maui East and Kapuni are being targeted to commence in 2027 by the operators. If CCS is initiated from 2027, then the following scenarios should be considered:

Scenario 1. Kapuni follows forecast 2P production profiles; natural gas supply declining steadily out to 2048. This would produce 0.75 Mt of CO₂ during the 2027–2030 period, and 0.56 Mt of CO₂ during the 2031–2035 period. Should Maui East commence operations by 2027, up to 1.36 Mt of CO₂ would be produced during the 2027-2030 period and 1.7 Mt of CO₂ produced during the 2031-2035 period.

Scenario 2. Maui East does not come online at all. Consequently, no uplift in natural gas production and associated emissions occur at Maui East. Kapuni follows forecast 2P production profiles; natural gas supply declining steadily out to 2048. This would produce 0.75 Mt of CO₂ during the 2027–2030 period, and 0.56 Mt of CO₂ during the 2031–2035 period.

Scenario 3. Wider industrial activity, albeit less mature than initiatives at Kapuni and Maui East, could investigate additional depleted reservoirs in the onshore Taranaki Basin (e.g. TAWN, RKM, Pohokura fields) for complementary CCS / CCUS initiatives.

Between 2027 and 2035, a total of 4.4 Mt of emissions associated with natural gas production could possibly be sequestered through CCS activity if there was a legislative framework that permits this and it was considered economically feasible.





Figure 3-1. Cumulative CO₂ production profile for Maui East and Kapuni fields



CCS facility	Operator CCS commencement target date	(Mt) (4 years of capture)	(Mt) (5 years of capture)
Todd	2027	0.75	0.56
OMV	2027	1.36	1.70
<i>Total</i>		<i>2.11</i>	<i>2.26</i>

Figure 3-2. Emission reduction budgets – pathway with and without CCS

4 OMV (NZ) Ltd

OMV carry several development scenarios for CCS application. Bounded by terms of confidentiality, Wood Beca are only permitted to give reference to the base case scenario – noting a series of scenario's are currently under consideration.

4.1 Base Case – offshore CO₂ stripping and injection

The base case for CCS at Maui involves separation of CO₂ from gas extracted within the Maui East field. Extracted gas will be directed to a purpose-built separation and compression facility located on Maui A platform. Separated CO₂ will be transported to an injection well and injected into a depleted reservoir offshore within the Maui Field.

4.2 Technical considerations

The Wood Beca technical review conclusion is:

- The offshore CCS project at Maui East is technically feasible but reliant on membrane CO₂ capture technology, due to real estate constraints on the Maui A platform. The practical limitation is approximately 55 MMscfd hydrocarbon inflow which relates to ~ 0.34 Mtpa CO₂ injection. Note that

OMV have not yet carried out Maui East well flow rate tests. As such the planned capacity of the CCS project is currently an uncertainty. Should the well flow rate test prove higher Maui East rates, then OMV will need to constrain Maui East hydrocarbon production based on the CO₂ plant capacity. This will introduce a commercial risk (deferred revenue), however could be mitigated somewhat by planning for a longer Maui East late life production phase.

- The Maui East offshore CO₂ management strategy requires resolution of key technical risks relating to asset integrity, well re-use, CO₂ release dispersion and evacuation procedures.
- The risks for the base case CCS development appear smaller than alternative CCS development strategies at Maui East.
- The Maui East offshore CO₂ management strategy is 'stand-alone' (e.g. an isolated development catering only for Maui East gas). There is currently no CCS hub opportunity to increase the development capacity by enabling 3rd parties to access the Maui reservoir.

5 Todd Energy

5.1 Base Case – Kapuni CCS

The base case CO₂ management strategy is to capture the CO₂ associated with 100 MMscfd raw Kapuni gas feed using the existing Benfield trains (some upgrades may be required) and reinject the CO₂ with a single reinjection well into the existing K3E reservoir.

5.2 Technical considerations

Information shared by Todd has allowed Wood Beca to make the following assessment:

- The Kapuni CO₂ management strategy requires resolution of key HSSE risks relating to CO₂ release dispersion, plant evacuation procedures and pipeline approval. All other technical risks identified are considered 'business as usual' to be worked through the project engineering phases.
- The Kapuni CO₂ management strategy is currently 'stand-alone' e.g. an isolated development catering only for Kapuni gas. As such, the project is currently effective in reducing emissions from a major hydrocarbon contributor. A key opportunity exists to accommodate simple design changes early in the project to allow for future expansion and 3rd party emitter access to the K3E reservoir for CO₂ storage. Examples include adequate tie-in points, custody transfer metering / allocation considerations, a pipeline diameter review and development of a fluid specification for engagement of regional industry.

6 Class 5 Cost Estimations

6.1 Overall cost of CCS in New Zealand (onshore and offshore)

6.1.1 Summary table: type scenario (e.g. onshore New Zealand)

Table 6-1 shows the estimated Class 5 lifecycle cost (-50% / +100%) for an onshore New Zealand CCS facility of 1 Mtpa capacity, 1 km pipeline and 20 year field life **scenario**. Note that costs are highly dependent on site specifics and don't include a range of ancillary project costs including the costs for, re use of existing equipment and consenting or any legislative processes as noted in detail in section 6.1.3. The values presented in Table 6-1 below are designed assuming a new membrane or amine-based capture system is required. The detailed analysis of these costs can be found in Appendix 3.

	Capture (in millions)	Compression (in millions)	Transportation (in millions)	Storage (in millions)	Contingency (in millions)	Price per tonne (\$NZD/tonne CO ₂)
Capex	\$190	\$66	\$2	\$36	\$88	\$30
Annual Opex	\$6	\$2	\$0	\$1		

Table 6-1 Summary table for onshore CCS *scenario* - 1 Mtpa capacity, 1 km pipeline, 20 year field life

6.1.2 Approach to cost estimate

There is insufficient data received from the Operators to enable an independent cost estimate (greater than Class 5) of specific CCS projects. Such a review will entail detailed analysis and enhanced access to proprietary data. A generic approach has been taken to generate cost information to illustrate the future issue for the whole of New Zealand industry and not just a particular or select industry.

Wood Beca has provided OOM CAPEX information either in the form of costed scenarios or cost metrics (dollar per unit).

A cost estimate accuracy is not provided for OOM CAPEX estimates. The information relies heavily on industry benchmarks, analogues and judgment with capacity factoring which aligns to the outer bounds of an AACE Class 5 (-50% / +100%), however this is not guaranteed. The OOM estimate is appropriate for strategic business planning, market studies and assessment of initial viability.

A simple building block approach is taken to allow development of case studies:

- Building block 1: cost of carbon capture
- Building block 2: cost of carbon compression
- Building block 3: cost of carbon transportation (pipelines)
- Building block 4: cost of carbon injection

6.1.3 Common basis of estimate

Costs have been developed by Wood Beca based on adjustment of equipment sizes from previous Wood studies/projects. Thereafter, design & PMT, bulks, fabrication, construction, commissioning, and owner's costs have been factored against the equipment procurement to obtain TIC. This factoring method is known as the Lang factor. The Lang Factor used is 3.0.

- The OOM estimates reflect industry experience of productivity and labour rates in the identified locations.
- The OOM estimates assume onshore site locations do not require significant groundwork prior to construction.
- The OOM estimates assume that all services, such as power, water and drainage are available at the site location.

The reference datasets are based on costs/estimates from 2017-21. An inflation factor is included at 15% for 2022. All costs are provided for 4th quarter 2022. Costs exclude forward escalation.

Growth and contingency are not factored into the individual building blocks.

This estimate has been prepared in New Zealand Dollars. The following foreign exchange conversions have been used where necessary: Although in New Zealand Dollars estimates are based on internal costs with no factor applied for specific new Zealand or site conditions.

Currency	Conversion
GBP to NZD	1.95
AUD to NZD	1.08
USD to NZD	1.66

Table 6-2 Q4 2022 average exchange rates (OFX, 2022)

The OOM estimates exclude:

- Infrastructure upgrades, demolition, or decommissioning
- Land costs, permits, consenting costs, surveys
- Sparing, commissioning, delays due to abnormal weather
- Past and current owners' costs, duty & Tax, royalties, and license fees
- Buildings, civil and utility works

All OOM cost look-up plots are provided only to support viability assessment and are not to be relied upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

6.1.4 Building block 1a: Cost of carbon capture from natural gas processing

Membrane based capture plant

The Operators engaged for the project are both considering CCS projects for natural gas process plants i.e., to capture and sequester the CO₂ arising from production of hydrocarbons.

Feedback from the Operators engaged is a preference for membrane CO₂ removal plant either due to offshore real estate constraints, or as a technology test challenge to exiting solvent-based CO₂ removal plants. On this basis, Wood Beca have estimated the OOM TIC for a membrane CO₂ capture plant.

Amine based capture plant

Amine solvent-based CO₂ capture has a wider track record for acid gas removal from natural gas processing plants. To give a direct comparison with the membrane technology, the OOM CAPEX has been estimated from an analogue FEED project (confidential).

Assumptions for the cost analysis of membrane and amine capture technologies are detailed in Appendix 3.




Figure 6-1. Scaled CO₂ capture cost (OOM), 2022 basis

6.1.5 Building block 1b: Cost of carbon capture from industrial emitters

Wood Beca have elected to exclude estimation of CO₂ capture from industrial emitters. CO₂ capture for local industry is highly bespoke to the specific characteristics of the emitted stream, with different processes and treatment systems required for pre-combustion, post-combustion, and oxy-combustion sources. It must be noted though, that additional to natural gas production facilities, industrial emitters of CO₂ (though not modelled in this review) represent potential sources that could support the wider concept of a CO₂ economy.

6.1.6 Building block 2: Cost of carbon compression

An internal cost estimate tool developed for CO₂ compression equipment has been used for calculation purposes. Refer to Appendix 3 for further information.





Figure 6-2. Scaled CO₂ compression cost (OOM), 2022 basis

6.1.7 Cost of transportation (pipelines) - onshore

An internal cost estimate tool developed for CO₂ pipeline transportation has been used. More information on the tool and basis of calculation is available in Appendix 3.

Selected USA CO₂ pipeline installation costs are provided which show a reasonable match to the Wood Beca order of magnitude estimate.



Rate (Mtpa)	0.2	0.4	0.6	0.8	1	1.2	1.5	2	5
Size (inch)	4	6	6	8	8	8	10	10	16
Pressure Drop (bar)	20.2	10.4	23.3	10.4	16.1	23.2	11.4	20.2	15.8
Velocity (m/s)	0.9	0.9	1.3	1.0	1.3	1.5	1.2	1.6	1.8


Figure 6-3. Onshore pipeline cost (OOM), 132 bar design pressure, dense phase pipeline graph and line size guidance (40km 120 bar dense phase pipeline)

The pipeline cost metric is very high at low flowrates, with the cost metric decreasing significantly with increasing flow. For example, a pipeline for *0.25 Mtpa*, 40 km (4 inch), 20 year field life has a CAPEX of \$59 NZD / tonne CO₂ stored where as a pipeline for *1.0 Mtpa*, 40 km (8 inch), 20-year field life has a CAPEX of \$25 NZD / tonne CO₂ stored.

6.1.8 Cost of transportation (pipelines) - offshore

As per the onshore pipeline estimate, an internal cost estimate tool developed for CO₂ pipeline transportation has been used (refer to Appendix 3).

Total installed costs (per km) estimate is provided in Figure 6-4 as a function of pipeline diameter, based on a 120 bar working pressure (144 bar design pressure) dense phase pipeline. This transportation condition is considered representative of the majority of use cases for offshore NZ CCS.



Rate (Mtpa)	0.2	0.4	0.6	0.8	1	1.2	1.5	2	5
Size (inch)	4	6	6	8	8	8	10	10	16
Pressure Drop (bar)	20.2	10.4	23.3	10.4	16.1	23.2	11.4	20.2	15.8
Velocity (m/s)	0.9	0.9	1.3	1.0	1.3	1.5	1.2	1.6	1.8

Figure 6-4. Offshore pipeline cost (OOM), 144 bar design pressure, dense phase pipeline graph and line size guidance (40km 120 bar dense phase pipeline)

6.1.9 Cost of injection

Costs for injection have been estimated by Wood Beca based on previous New Zealand studies/projects. A cost of \$12M NZD has been assumed for drilling an onshore well of 0.5 Mtpa maximum capacity. N+1 well philosophy should be assumed. Cost of injection is much higher for offshore drilling.

6.1.10 All in cost per tonne (onshore)

The Class 5 cost for an onshore CCS facility in New Zealand ranges from \$30 - \$110/tonne CO₂ (Table 6-3). This cost estimate is based on a capacity of 0.25 – 1 Mtpa, with a pipeline length of 1 – 80km, assuming a 20 year facility life. The Kapuni – Methanex LTS line fits within this range of pipeline lengths. This cost includes 3% of CAPEX for annual operation and maintenance costs for capture, compression and injection equipment and 1% of CAPEX for annual operation and maintenance costs for onshore pipeline. A contingency factor of 30% CAPEX has been applied. Wood Beca have elected not to provide a Class 5 cost estimate for offshore CCS due to a lack of suitable data, however, note that the cost of executing an offshore CCS project is expected to be much higher than onshore. These costs are generated for CO₂ arising from natural gas processing (concentrated CO₂) rather than dilute CO₂ flue gas sources (e.g. power station), which have a higher cost of capture as well as having cost penalties due to inefficiencies (energy diversion away from the product). Therefore, these cost metrics are only appropriate for CCS from natural gas processing and cannot be used for other industrial CO₂ sources.

Our conclusions show there is a large range in the cost of CCS. These conclusions are consistent with the Global CCS Institute 'Technology Readiness and Costs of CCS' report. Global CCS Institute conclude that large scale natural gas processing is a low-cost opportunity and CCS may be less than \$33 NZD/ tonne CO₂ (assuming an exchange rate of 1.66 NZD to USD).

Below parametric shows cost change for natural gas CCS systems as a function of capacity and pipeline distance. The capacity of the system has first order impact on cost, pipeline length is second order.

20 years	Mtpa			
	0.25	0.5	1	
1km	50	36	28	\$ NZD / tonne CO ₂ stored
10km	57	40	30	\$ NZD / tonne CO ₂ stored
20 km	64	43	31	\$ NZD / tonne CO ₂ stored
40 km	78	50	35	\$ NZD / tonne CO ₂ stored
60 km	93	58	39	\$ NZD / tonne CO ₂ stored
80 km	107	65	42	\$ NZD / tonne CO ₂ stored

Table 6-3 Onshore CCS Class 5 cost estimates: variation and impact on cost (+30% contingency applied on overall whole scope TIC n+1 well philosophy, 0.5 Mtpa capacity per well assumption)

6.2 Implication with ETS

There are a number of forecasts and shadow price models for ETS price and benchmark values. Figure 6-5 presents the historic NZ ETS price alongside two forecasts, Tūi and Kea from the New Zealand Business Energy Council (ASEAN Climate Change and Energy Project, 2008), and a shadow emissions price from the Ināia Tonu Nei demonstration path (Business NZ Energy Council, 2021).

The shadow price value of \$140 (in 2019 dollars) is from the demonstration path from the Climate Change Commission's Ināia Tonu Nei advice which forms part of the draft advice to government. The Climate Change Commission's recommended emission budgets were based on this demonstration path, which should be interpreted as a shadow emissions price, rather than necessarily an explicit price in the NZ ETS (Climate Change Commission, 2022).

ETS shadow pricing and corresponding observations:

- CCS stand-alone costs would appear to provide options to mitigate ETS liability and emission reduction for large scale natural gas producers such as Todd and OMV
- The price of ETS in Kea and Tūi forecasts increase steadily over the next decade, this would make CCS more economic




Figure 6-5. ETS historic, forecasted and shadow pricing (box plot represents Class 5 cost estimates for CCS facilities of 0.2 – 1.2 Mtpa capacity, 0.5 – 40 km pipeline length and 20 year field life)

7 Additional Considerations

7.1 A CO₂ economy

CO₂ is a valuable resource. Management of this, in a collective sense, will allow for known and suspected surplus *and* shortage of CO₂ to be balanced under the broader concept of a CO₂ economy. On one hand, as current emitters seek to limit their emission liability, other large scale CO₂ consumers seek enduring business certainty. The role of CCUS and CCS should be treated as complementary elements to managing this valuable resource. Wood Beca make the following comments:

- By establishing a network, initially in the Taranaki region, a phased approach may support the case to recommission the Kapuni – Methanex LTS pipeline. Connected by way of a shared pipeline:
 - Current chemical production of urea and methanol in Taranaki rely on CO₂ feedstock provided through affordable and reliable supply of natural gas.
 - Future chemical production of urea, methanol, hydrogen, and ammonia utilising Green Hydrogen will require large volumes of introduced electricity, and in the case of urea and methanol production – access to CO₂. Large scale offshore wind derived electricity could integrate into the concept of a CO₂ economy.
 - Note that the success of a CCUS hub in Taranaki depends on whether local chemical manufacturers will accept fossil-based CO₂ rather than biogenic CO₂.
- Surplus to CCUS requirements, non-utilised CO₂ - derivatives of emissions and/or post combustion process from industrial emitters, become immediate CCS (both permanent and temporary storage) candidates.

8 Concluding Remarks and Recommendations

Since 2019, global carbon capture capacity (concept, under construction and operating), has increased by a factor of four up to 320Mt from 80Mt.

This review, consistent with global increases in CCUS / CCS research, has under conditions of limited time and breadth of data made available, allowed Wood Beca to reach the following perspectives, subject to final decisions to be made by private asset owning organisations operating in the constraints at the time. Noting work is required to confirm the assumptions made prior to any investment decision:

8.1 Is CCS technically and economically viable in New Zealand?

- CCS reflects known technology capable of successful application at both Maui and Kapuni late life fields.
- Sufficient reservoir void space exists to receive injected CO₂ at the Maui and Kapuni fields.
- Wood Beca has provided Class 5 cost estimates for CCS application in New Zealand. Arriving at a potential value of \$30 NZD for a simplified onshore Taranaki *type scenario*. It must be noted though, a range of CCS costs in Taranaki (\$30 - \$110) exist, highly dependent on location, reservoir depth and quality of CO₂. When compared against current and forecast ETS cost, ranges of CCS cost provide compelling grounds for favourable consideration.
- A consequence of any sanctioned CCS application at:
 - Maui East may:
 - Support future CO₂ economy considerations, which could include all Maui associated infrastructure.
 - Kapuni may:
 - Support broader concepts of a CO₂ economy by utilising, amongst options, the Kapuni to Methanex 070 pipeline infrastructure.
 - Other:
 - Complementary source / sink pairs within the Taranaki region or further afield create a broader portfolio of optionality.

8.2 What contribution can sequestration make to emissions reductions, security of supply and energy affordability?

Combined CCS programmes envisaged for Maui and Kapuni have the potential to reduce emissions after 2027, when operating.

- Significant emissions reductions could be made with CCS (provided this is enabled by legislation).
- Production of natural gas in New Zealand can continue to provide security of supply to energy users well into the late 2030's. Natural gas is likely to be required but CCS enables it to occur with lower emissions.
- End of field life forecasts at Maui and Kapuni, *currently* occur before majority electrification replacement (e.g. large-scale offshore wind) conceivably takes effect. Extension of field life through remaining 2P reserves and 2C resource upgrades using capture of CO₂ will provide energy security during the transition to electrification.

- Noting the Maui and Kapuni fields respectively contribute ~ 18% and 5% of New Zealand's daily natural gas consumption (MBIE, 2021b); prolonged production profiles could mitigate natural gas price increase in an otherwise shortening market.

8.3 How does a pathway that includes sequestration compares to alternative scenarios that do not?

A path that does not include methods of sequestration will leave potential options for CO₂ emissions reduction off the table. As demonstrated above there are large numbers of CCS and CCUS projects being implemented globally as the world transitions to net zero.

A path including sequestration allows for a transition to renewables by prolonging the end of field life. Thus, supporting energy security, affordability, and sustainability.

In the context of CCUS, growing demand for e-chemical production, including urea and methanol will require access not only to electricity, but CO₂.

- Opportunity for a CO₂ economy exists within the Taranaki region to service the requirements of current and future CCUS initiatives, while supporting both permanent and temporary CCS requirements.

9 References

- ASEAN Climate Change and Energy Project. (2008). *Renewable Energy and Energy Efficiency*. February, 41–58. <https://doi.org/10.14217/smalst-2008-4-en>
- Beca. (2023). *Internal Ballance presentation*.
- Business NZ Energy Council. (2021). *Draft first package of advice to the Government to the Climate Change Commission*.
- Capture6. (2022). *DAC and Storage*. <https://capture6.org/>
- Climate Change Commission. (2022). *Advice on NZ ETS unit limits and price control settings for 2023-2027 (July 2022)*. July 2022, 1–98. <https://www.climatecommission.govt.nz/our-work/advice-to-government-topic/nz-ets/our-advice-on-the-nz-ets/nz-ets-unit-limits-and-price-control-settings-for-2023-2027/full-report/>
- Concept Consulting. (2022). *Gas Supply and Demand Projections*.
- Global CCS Institute. (2022). *Status Report*. <https://status22.globalccsinstitute.com/2022-status-report/introduction/>
- MBIE. (2021a). *Energy in New Zealand*. <https://www.mbie.govt.nz/building-and-energy/energy-and-natural-resources/energy-statistics-and-modelling/energy-publications-and-technical-papers/energy-in-new-zealand/>
- MBIE. (2021b). *Petroleum Reserves Data*. <https://www.mbie.govt.nz/building-and-energy/energy-and-natural-resources/energy-statistics-and-modelling/energy-statistics/petroleum-reserves-data/>
- McKinsey & Company. (2022). *Global Energy Perspective*. <https://www.mckinsey.com/industries/oil-and-gas/our-insights/global-energy-perspective-2022>
- Methanex. (2021). *Methanex Sustainability Report*. [https://www.methanex.com/sites/default/files/responsible-care/Methanex 2021 Sustainability Report_Updated.pdf](https://www.methanex.com/sites/default/files/responsible-care/Methanex%2021%20Sustainability%20Report_Updated.pdf)
- Ministry for the Environment. (2022a). *Emission budgets and the emission reduction plan*. <https://environment.govt.nz/what-government-is-doing/areas-of-work/climate-change/emissions-budgets-and-the-emissions-reduction-plan/>
- Ministry for the Environment. (2022b). *New Zealand's Interactive Emissions Tracker*. <https://emissionstracker.environment.govt.nz/#NrAMBoEYF12TwCIByBTALo2wBM4eiQAc2RSWcAnO>

dNEA

OFX. (2022). *Exchange Rates*. ofx.com

Scott, A., Oze, C., Shah, V., Yang, N., Shanks, B., Cheeseman, C., Marshall, A., & Watson, M. (2021). Transformation of abundant magnesium silicate minerals for enhanced CO₂ sequestration. *Communications Earth and Environment*, 2(1), 1–6. <https://doi.org/10.1038/s43247-021-00099-6>

Transpower. (2022). *Transpower seeks investment to power New Zealand's energy transition*. <https://www.transpower.co.nz/news/transpower-seeks-investment-power-new-zealands-energy-transition#:~:text=Industry forecasts%2C including our own,achieving net zero carbon emissions.>”



Cost of CCS in New Zealand

In support of the Gas Transition Plan

Approach to cost estimate

Because of the confidentiality agreements signed, there is insufficient data received from NZ Operators to enable an independent cost estimate of specific CCS projects. A generic approach is therefore taken to generate cost information to help illustrate future issues for the whole of New Zealand industry and not just a particular or select industry.

Wood Beca has elected to provide Order of Magnitude (OOM) CAPEX information either in the form of costed scenarios or cost metrics (dollar per unit). A detailed breakdown of the working behind these costs is not provided or considered relevant to the objective of this high-level study.

A cost estimate accuracy is not provided for OOM CAPEX estimates. The information relies heavily on industry benchmarks, analogues and judgment with capacity factoring which aligns to the outer bounds of an AACE Class 5 (-50% / +100%), however this is not guaranteed. The OOM estimate is appropriate for strategic business planning, market studies and assessment of initial viability.

A simple building block approach is taken to allow development of case studies:

- Building block 1: cost of carbon capture – *generalised cost for both onshore and offshore*
- Building block 2: cost of carbon compression – *generalised cost for both onshore and offshore*
- Building block 3: cost of carbon transportation (pipelines) – *onshore and offshore costs presented separately*
- Building block 4: cost of carbon injection – *onshore costs presented only*

Common basis of estimate

Costs have been developed by Wood Beca based on adjustment of equipment sizes from previous Wood studies/projects. Thereafter, design & PMT, bulks, fabrication, construction, commissioning, and owner's costs have been factored against the equipment procurement to obtain Total installed Cost (TIC). This factoring method is known as the Lang factor. The Lang Factor used is 3.0.

The OOM estimates reflect industry experience of productivity and labour rates in the identified locations.

The OOM estimates assume onshore site locations do not require significant groundwork prior to construction.

The OOM estimates assume that all services, such as power, water and drainage are available at the site location.

The reference datasets are based on costs/estimates from 2017-21. An inflation factor is included at 15% for 2022. All costs are provided for 4th quarter 2022. Costs exclude forward escalation.

Growth and contingency are not factored into the individual building blocks.

This estimate has been prepared in New Zealand Dollars. Although in New Zealand Dollars, estimates are based on internal costs with no factor applied for specific New Zealand or site conditions.

The foreign exchange conversions used are shown in Table 1.

Table 1 Currency conversions

Currency	Conversion
GBP to NZD	1.95
AUD to NZD	1.08
USD to NZD	1.66

Common basis of estimate

The OOM estimates exclude:

- Infrastructure upgrades, demolition, or decommissioning
- Land costs, permits, consenting costs, surveys
- Sparring, commissioning, delays due to abnormal weather
- Past and current owners' costs, duty & Tax, royalties, and license fees
- Buildings, civil and utility works

All OOM cost look-up plots are provided only to support viability assessment and are not to be relied upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

Cost of carbon capture from natural gas processing (onshore and offshore)

Membrane based capture plant

The Operators engaged for the project are both considering CCS projects for natural gas process plants i.e., to capture and sequester the CO₂ arising from production of hydrocarbons.

Feedback from the Operators engaged is a preference for membrane CO₂ removal plant either due to offshore real estate constraints, or as a technology test challenge to exiting solvent-based CO₂ removal plants. On this basis, Wood Becca have estimated the OOM TIC for a membrane CO₂ capture plant.

Capex for a circa. 0.2 Mtpa membrane-based capture plant has been estimated from in-house membrane technology datasets.

- The equipment cost of the membrane, permeate compressor and other associated equipment as shown in the Figure 1 has been estimated by pro-rating on the CO₂ loading of Stream B
- The pre-treatment equipment cost has been assumed to be 25% of the membrane cost




Figure 1 Typical 2-Stage Membrane Configuration

Cost of carbon capture from natural gas processing (onshore and offshore)

Table 2 *CO₂ Loading Basis*

Stream	Pressure (barg)	Temperature (°C)	MMscfd	CO ₂ mol%	mtpa
A	55	29	37	32	0.23
B	53	34	52	38	0.38
C	3	40	12	95	0.21

For the system outlined in Figure 1 and the loading outline in Table 2, the OOM CAPEX is as follows:

Table 3 *Membrane Based Capture Plant - 0.2 MTPA CO₂*

Item	Million USD	Million NZD
Equipment Cost	13.0	21.6
Equipment Cost, 2022 Basis	14.9	24.8
TIC	39.0	64.7
TIC, 2022 Basis	44.9	74.5

The equipment cost is inclusive of the membranes, separators, compressors, coolers and pre-treatment allowance. The membrane cost alone represents approximately 50% of the equipment cost. Vendor data and benchmarks are confidential and cannot be shared, however the Table 3 data is generally aligned.

Cost of carbon capture from natural gas processing (onshore and offshore)

Amine based capture plant

Amine solvent-based CO₂ capture has a wider track record for acid gas removal from natural gas processing plants. To give a direct comparison with the membrane technology, the OOM CAPEX for a 0.2 Mtpa has been estimated from an analogue FEED project (confidential). The equipment cost has been estimated based on pro-rating the cost based on the CO₂ capture rate (0.55 Mtpa basis pro-rated for 0.2 Mtpa plant).

Table 4 Amine Based Capture Plant - 0.2 MTPA CO₂

Item	Million USD	Million NZD
Equipment Cost	16.5	27.4
Equipment Cost, 2022 Basis	19.0	31.5
TIC	49.5	82.2
TIC, 2022 Basis	57.0	94.6

Summary

A capture plant OOM cost look-up plot is provided in Figure 2, based on an industry standard scaling relationship. The plot is provided only to support viability assessment and is not rely upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

Cost of carbon capture from natural gas processing (onshore and offshore)




Figure 2 Scaled CO₂ Capture Cost (OOM), 2022 Basis

Cost of carbon capture from industrial emitters

Wood Beca have elected to exclude estimation of CO₂ capture from industrial emitters. CO₂ capture for local industry is highly bespoke to the specific characteristics of the emitted stream, with different processes and treatment systems required for pre-combustion, post-combustion, and oxy-combustion sources.

Cost of carbon compression (onshore and offshore)

An internal cost estimate tool developed for CO₂ compression equipment has been used. This is based on benchmarked vendor and project cost data collected over a period 2017 to 2021. This data is covered under confidentiality and cannot be shared. The following costing premise is considered:

- A range of captured CO₂ compression rate from 0.2 to 1.25 Mtpa
- A compressor inlet pressure of 3 bara
- A typical compressor discharge pressure of 120 bara. This is based on dense phase CO₂ transport over relatively 'close-coupled' systems i.e. the compression plant is adjacent (or within <10 km) of the CO₂ storage site. A range of 85 to 150 bar is typical to assure dense phase transport. Note:
 - Less than 85 bar risks two-phase conditions in the downstream pipeline and wells.
 - A discharge pressure greater than 150 bar may be required for longer distance CO₂ transport and may require a pump stage to provide the additional pressure.
- A multi-stage 1 x 100% compression train is costed. For the pressure increase considered (3 bara to 120 bara), typically 4 stages of compression will be required, with interstage cooling and liquid knock-out (separators) and an aftercooler.

A compression plant OOM cost look-up plot is provided in Figure 3. The plot is provided only to support viability assessment and is not rely upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

Cost of carbon compression (onshore and offshore)

As indication of utilities demand for compression from 3 bar to 120 bar, with discharge at 40°C;

- 0.2 Mtpa will require approximately 2.0 MW compression power and 4.9 MW cooling demand
- 1.0 Mtpa will require approximately 9.9 MW compression power and 30.7 MW cooling demand




Figure 3 Scaled CO₂ Compression Cost (OOM), 2022 Basis

Cost of transportation (onshore) - pipelines

- An internal cost estimate tool developed for CO₂ pipeline transportation has been used. The tool determines the pipeline size required based on CO₂ rate and the wall thickness required based on the working pressure. The pipeline costing then accounts for the following cost items based on industry benchmarked cost metrics (activity durations, unit costs):
 - Geotechnical and topographical route surveys
 - Materials: line pipe, internal, external, and concrete weight coating procurement
 - Installation: site set-up, right of way preparation and pipeline installation
 - Crossings: roads, rail, existing pipelines, and minor rivers
 - Miscellaneous activity fixed allowance (approximately 4.9 million NZD)
 - Project management and engineering
 - Fixed margin (10%) for spurs, offtakes, and pigging facilities
- The TIC OOM cost (per km) estimate is provided in Figure 4 as a function of pipeline diameter, based on a 120 bar working pressure (132 bar design pressure) dense phase pipeline. This transportation condition is considered representative of the majority of use cases for onshore NZ CCS.
- The plot is provided only to support viability assessment and is not rely upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.
- Industry cost analogues are difficult to obtain as the basis can be unclear (e.g., wall thickness / pipe schedule, environment, distance, diameter, installation date etc.). Selected USA CO₂ pipeline installation costs are provided which show a reasonable match to the Wood Beca OOM estimate.

Cost of transportation (onshore) - pipelines

A rough guide to line sizing is provided in Table 5. This is indicative only, specific to a 120 bar working pressure, 40 km dense phase pipeline. Flow assurance analysis is required for specific scenarios.




Figure 4 Onshore Pipeline Cost (OOM), 132 bar design pressure, dense phase pipeline

Table 5 Line size guidance, 40 km 120 bar dense phase pipeline

Rate	0.2	0.4	0.6	0.8	1	1.2	1.5	2	5
Size (inch)	4	6	6	8	8	8	10	10	16
Pressure Drop (bar)	20.2	10.4	23.3	10.4	16.1	23.2	11.4	20.2	15.8
Velocity (m/s)	0.9	0.9	1.3	1.0	1.3	1.5	1.2	1.6	1.8

Cost of injection (onshore)

Costs for injection have been estimated by Wood Beca based on previous New Zealand studies/projects. A cost of \$12M NZD has been assumed for drilling a well of 1 Mtpa maximum capacity. Cost of injection is higher for drilling offshore.

All in cost per tonne (onshore)

The Class 5 cost for an onshore CCS facility in New Zealand of 1 Mtpa capacity and 1 km pipeline is \$28/tonne, assuming a 20 year facility life. This cost includes 3% of CAPEX for annual operation and maintenance costs for capture, compression and injection equipment and 1% of CAPEX for annual operation and maintenance costs for onshore pipeline. A contingency factor of 30% CAPEX has been applied.

These costs are generated for CO₂ arising from natural gas processing (concentrated CO₂) rather than dilute CO₂ flue gas sources (e.g. power station), which have a higher cost of capture as well as having cost penalties due to inefficiencies (energy diversion away from the product). Therefore, these cost metrics are only appropriate for CCS from natural gas processing and cannot be used for other industrial CO₂ sources.

Our conclusions show there is a large range in the cost of CCS. These conclusions are consistent with the Global CCS Institute (GCI) 'Technology Readiness and Costs of CCS' report. GCI conclude that large scale natural gas processing is a low-cost opportunity and CCS may be less than \$33 NZD/ tonne CO₂ (assuming an exchange rate of 1.66NZD to USD).

Detailed Cost Analysis of CCS in New Zealand

All in cost per tonne (onshore)

Below parametric shows cost change for natural gas CCS systems as a function of capacity and pipeline distance. The capacity of the system has first order impact on cost, pipeline length is second order.

20 yrs	Mtpa			
	0.25	0.5	1	
1 km	50.1	36.1	27.8	NZD/tonne CO ₂ stored
10 km	56.6	39.4	29.5	NZD/tonne CO ₂ stored
20 km	63.8	43.0	31.3	NZD/tonne CO ₂ stored
40 km	78.3	50.3	35.0	NZD/tonne CO ₂ stored
80 km	107.1	64.9	42.4	NZD/tonne CO ₂ stored

Table 6 Variation and impact on cost (+30% contingency applied on overall whole scope TIC_{n+1} well philosophy, 0.5 Mtpa capacity per well assumption)

Cost of transportation (offshore) - pipelines

As per the onshore pipeline estimate, an internal cost estimate tool developed for CO₂ pipeline transportation has been used. The tool determines the pipeline size required based on CO₂ rate and the wall thickness required based on the working pressure. The pipeline costing then accounts for the following cost items based on industry benchmarked cost metrics (activity durations, unit costs):

- Pipeline routing: vessel mob/demob, geotechnical survey
- Materials: line pipe, internal, external, and concrete weight coating procurement
- 1 x shore crossing (typical open cut is assumed)
- Installation: vessel mob/demob (DSV, survey, support and lay vessels), pipeline trenching
- Allowance for crossings

The TIC OOM cost (per km) estimate is provided in Figure 5 as a function of pipeline diameter, based on a 120 bar working pressure (144 bar design pressure) dense phase pipeline. This transportation condition is considered representative of the majority of use cases for offshore NZ CCS.

The plot is provided only to support viability assessment and is not rely upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

The plot is provided only to support viability assessment and is not rely upon for project specific cost estimation. Every project is bespoke, and hence caution is required applying a generic approach.

Cost of transportation (offshore) – pipelines

Industry cost analogues are difficult to obtain as the basis can be unclear (e.g., wall thickness / pipe schedule, location, mob/demob durations, distance, diameter, installation date etc.). Selected offshore CO₂ pipeline installation costs are provided which show a reasonable match to the Wood Beca OOM estimate, albeit on the lower side. There is one high outlier (16”) noting this is for a short (<30 km) 230 bar design pressure pipeline with high material costs.




Figure 5 Offshore Pipeline Cost (OOM), 144 bar design pressure, dense phase pipeline

Detailed Cost Analysis of CCS in New Zealand

Case 1: Example of Class 5 cost estimate for onshore CCS facility; 0.75 Mtpa and 0.5km pipeline.

Analysis										
Case:	0.75	mtpa								
	0.5	km pipeline								
	8	inch								
	20	year project life								
	n+1	well philosophy								
	30%	contingency								
	10%	discount factor								
			CAPEX (MMNZD)				Annual OPEX (MMNZD)			
	mtpa	Cap	Comp	Transp	Inj	Cont	Cap	Comp	Transp	Inj
	0.75	159	53	1	36	75	5	2	0	1
	CAPEX	324	MMNZD	PV (no CAPEX phasing)						
	OPEX	7	MMNZD	per annum						
	OPEX	149	MMNZD	over field life (not discounted)						
	OPEX	85.1	MMNZD	discounted						
	CO2 stored	15	mTe							
	Price	31.6	NZD/TeCO2							
	Price	27.3	NZD/TeCO2							

Case 2: Example of Class 5 cost estimate for onshore CCS facility; 1 Mtpa and 20 km pipeline.

Analysis										
Case:	1	mtpa								
	20	km pipeline								
	8	inch								
	20	year project life								
	n+1	well philosophy								
	30%	contingency								
	10%	discount factor								
			CAPEX (MMNZD)				Annual OPEX (MMNZD)			
	mtpa	Cap	Comp	Transp	Inj	Cont	Cap	Comp	Transp	Inj
	1	189	66	49	36	10%	6	2	0	1
	CAPEX	442	MMNZD	PV (no CAPEX phasing)						
	OPEX	9	MMNZD	per annum						
	OPEX	184	MMZD	over field life (not discounted)						
	OPEX	85.1	MMZD	discounted						
	CO2 stored	20	mTe							
	Price	31.3	NZD/TeCO2							
	Price	26.3	NZD/TeCO2							

Case 3: Example of Class 5 cost estimate for onshore CCS facility; 0.2 Mtpa and 20 km pipeline.

Analysis										
Case:	0.2	mtpa								
	20	km pipeline								
	4	inch								
	20	year project life								
	n+1	well philosophy								
	30%	contingency								
	10%	discount factor								
			CAPEX (MMNZD)				Annual OPEX (MMNZD)			
	mtpa	Cap	Comp	Transp	Inj	Cont	Cap	Comp	Transp	Inj
	0.2	72	20	48	24	49	2	1	0	1
	CAPEX	213	MMNZD	PV (no CAPEX phasing)						
	OPEX	4	MMNZD	per annum						
	OPEX	79	MMNZD	over field life (not discounted)						
	OPEX	85.1	MMNZD	discounted						
	CO2 stored	4	mTe							
	Price	73.2	NZD/TeCO2							
	Price	74.6	NZD/TeCO2							

Case 4: Example of Class 5 cost estimate for onshore CCS facility; 1 Mtpa and 1 km pipeline.

Analysis										
Case:	1	mtpa								
	1	km pipeline								
	8	inch								
	20	year project life								
	n+1	well philosophy								
	30%	contingency								
	10%	discount factor								
			CAPEX (MMNZD)				Annual OPEX (MMNZD)			
	mtpa	Cap	Comp	Transp	Inj	Cont	Cap	Comp	Transp	Inj
	1	189	66	2	36	33	6	2	0	1
	CAPEX	381	MMNZD	PV (no CAPEX phasing)						
	OPEX	9	MMNZD	per annum						
	OPEX	175	MMZD	over field life (not discounted)						
	OPEX	85.1	MMZD	discounted						
	CO2 stored	20	mTe							
	Price	27.8	NZD/TeCO2							
	Price	23.3	NZD/TeCO2							